Amendments to the Claims

This listing of claims will replace all prior versions and listings, of claims in the application.

Listing of Claims

1-20. (Previously Canceled)

21. (Currently Amended): An electronic whiteboard having flexible membrane electromagnetic induction generating device, including an electronic whiteboard main unit having a writing layer as surface, a bottom support bracket layer as bottom, an input induction section, a recognition controlling circuit, a signal output device inside between the said two layers and a frame around, and also including an input pen, characterized in that: said induction section is composed of a covering layer, an electromagnetic induction generating layer and a bottom support bracket layer, wherein the base layer of the electromagnetic induction generating layer is an insulated flexible membrane which can be a film material, the surfaces of membrane are printed with an electromagnetic induction receiving antenna array which is induction antenna cells distributed along X axis and Y axis, thereby a flexible membrane electromagnetic induction generating layer is constituted, the output of that electromagnetic induction generating layer is connected to the recognition controlling circuit, and the input pen has a radio signal generating device;

said signal output device is a cable connecting device which is a cable javomg

USB joint interface or a wireless data communicating device which is a radio

frequency transceiver, and said signal output device is connected to a computer
and/or a printer and/or a data storing equipment directly;

Appl. No. 10/500,479

Amdt. Dated November 8, 2007

Reply to Office Action of May 1, 2007

Attorney Docket No. 88538.0001

Customer No.: 26021

said induction antenna array cells are the cells printed on the two sides of the

membrane surface respectively;

more than one layer of induction antenna cells along X axis and Y axis are

the cells printed on the two sides of the membrane surface and the layers are

insulated from each other; and

the intervals between the induction antenna cells of each layer are different

for more than one layer of induction antenna cells.

22. (Previously Presented): An electronic whiteboard having flexible

membrane electromagnetic induction generating device as cited in claim 21,

characterized in that: said recognition controlling circuit is set on a PCB (printed

circuit board), and the antenna's output port of said flexible membrane

electromagnetic induction generating layer is spliced or plugged or welded to the

corresponding input pin on the PCB (printed circuit board).

23. (Currently Cancelled)

24. (Currently Cancelled)

25. (Currently Cancelled)

26. (Previously Presented): An electronic whiteboard having flexible

membrane electromagnetic induction generating device as cited in claim 21,

characterized in that: said induction antenna cell is silver paste material or mixture

material of silver paste and carbon paste.

Page 3 of 11

Appl. No. 10/500,479 Amdt. Dated November 8, 2007 Reply to Office Action of May 1, 2007 Attorney Docket No. 88538.0001 Customer No.: 26021

27. (Previously Presented): An electronic whiteboard having flexible membrane electromagnetic induction generating device as cited in claim 21, characterized in that: a shielding layer can be provided behind said electromagnetic induction generating layer to increase the anti-interference capability.

- 28. (Currently Cancelled)
- 29. (Currently Cancelled)
- 30. (Currently Cancelled)
- 31. (Previously Presented): An electronic whiteboard having flexible membrane electromagnetic induction generating device as cited in claim 21, characterized in that: the radio signal generating device of said writing input pen is an electromagnetic wave generating device.
- 32. (Previously Presented): An electronic whiteboard having flexible membrane electromagnetic induction generating device as cited in claim 21, characterized in that: said radio signal generation device of the writing input pen has a RF generating or receiving device, corresponding RF receiving or generating device is provided on the whiteboard main unit.